

BS-220 Long Range CCD Scanner

Features :

- Hands-free stand for presentation scanning (optional)
- Specially designed to deliver high-end performance at the lowest possible price.
- Multi-interface support
- Flash memory-facilitates updates
- GS1 Databar support



Made in Taiwan

Specifications

Interface		RS232, USB HID, USB COM, PS2
CPU		32 bit
Reading Performance	Readable Barcode Format	EAN-8, EAN-13, UPC-A, UPC-E, EAN/UPC Add-on, Code-93, Code-32, Code-32, UCC/EAN/Code-128, INDUSTRIAL-25, Interleaved-25, Martix-25, Codabar/Nw7, MSI/PLESSEY RSS (GS1 Databar)
	Resolution	4 mil
	PCS Value	Up to 0.3
	Depth of Field	50 – 250 mm
	Light Source	630 nm Red LED LAMP
	Read Sensor	Linear CCD Image Sensor
	Scanning Rate	100scans/sec × 2 cycles
	Decoding Rate	Real-Time 200 scans/sec
	Scanning Performance	200 scans/sec
Programming Configuration	Programming Manual or Download via USB COM I/F & ISP Flash ROM BIOS software update	
Indicator		Green LED and beep
Weight		95g (without cable)
Working Temperature		0°C – 50°C
Environment Humidity		10% - 90% RH
Electrical Unit	RFI/EMI	FCC Class A / CE
	Voltage	DC 5V ± 5%
	Power Consumption	65-75Ma
	Stand by	5 uA (0.005mA) via keyboard mode